

# Table of Contents

<b>BS2_GetCard1xConfig</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1

[Configuration API](#) > [BS2\\_GetCard1xConfig](#)

---

## BS2\_GetCard1xConfig

Retrieves v1 Template on Card settings from the device. This feature is implemented to read Template on Cards already issued from a v1 device. It does not allow a v2 device to issue a template on card in a v1 layout.

### Declaration

```
#include "BS_API.h"

int BS2_GetCard1xConfig(void* context, uint32_t deviceId, BS1CardConfig* config);
```

[See BS1CardConfig Structure](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [Out] *config* : v1 template on card settings pointer

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

From:  
<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:  
[http://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2\\_getcard1xconfig&rev=1498615510](http://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_getcard1xconfig&rev=1498615510)

Last update: **2017/06/28 11:05**