

# Table of Contents

<b>BS2_SetEventConfig</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1

[Configuration API](#) > [BS2\\_SetEventConfig](#)

---

## BS2\_SetEventConfig

Stores image log filter settings on the device.

### Info

Available for devices that support image log **FaceStation F2, FaceStation 2, BioStation A2, X-Station 2, and BioStation 3.**

## Declaration

```
#include "BS_API.h"

int BS2_SetEventConfig(void* context, uint32_t deviceId, BS2EventConfig* config);
```

[See BS2EventConfig Structure](#)

## Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : Image log filter configurations pointer.

## Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

From:  
<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2\\_seteventconfig&rev=1719795747](https://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_seteventconfig&rev=1719795747)

Last update: **2024/07/01 10:02**