

BS2_ClearDeviceZoneAccessRecord	1
.....	1
.....	1
.....	1
.....	1
.....	1
.....	1

[Zone Control API](#) > [BS2_ClearDeviceZoneAccessRecord](#)

BS2_ClearDeviceZoneAccessRecord

Ethernet

BioStation 2 (1.5.0 only)
BioStation A2 (1.4.0 only)
BioEntry P2 (1.0.0 only)

```
#include "BS_API.h"

int BS2_ClearDeviceZoneAccessRecord(void* context, uint32_t deviceId,
uint32_t zoneID, char* uids, uint32_t uidCount);
```

- [In] *context* : Context
- [In] *deviceId* :
- [In] *zoneID* :
- [In] *uids* : user ID
- [In] *uidCount* : user ID

BS_SDK_SUCCESS, 가

[BS2_GetDeviceZone](#)
[BS2_GetAllDeviceZone](#)
[BS2_SetDeviceZone](#)
[BS2_RemoveDeviceZone](#)
[BS2_SetAntiPassbackZone](#)
[BS2_RemoveAllDeviceZone](#)
[BS2_SetDeviceZoneAlarm](#)
[BS2_ClearAllDeviceZoneAccessRecord](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk./doku.php?id=ko:bs2_cleardevicezoneaccessrecord

Last update: **2018/03/22 10:53**