

BS2_RemoveAuthOperatorLevelEx 1

..... 1

..... 1

..... 1

..... 1

[Device API](#) > [BS2_RemoveAuthOperatorLevelEx](#)

BS2_RemoveAuthOperatorLevelEx

[+ 2.6.3] userIDs

[BS2_SetAuthConfig](#), [BS2_GetAuthConfig](#) 10
1000
[BS2_SetAuthConfig](#), [BS2_GetAuthConfig](#) 가

```
#include "BS_API.h"
```

```
int BS2_RemoveAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId,
BS2_USER_ID* userIDs, uint32_t userIDCount);
```

- [In] *context* : Context
- [In] *deviceId* :
- [In] *userIDs* :
- [In] *userIDCount* :

BS_SDK_SUCCESS , 가

- [BS2_GetAuthOperatorLevelEx](#)
- [BS2_GetAllAuthOperatorLevelEx](#)
- [BS2_SetAuthOperatorLevelEx](#)
- [BS2_RemoveAuthOperatorLevelEx](#)
- [BS2_RemoveAllAuthOperatorLevelEx](#)

From:
<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:
https://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_removeauthoperatorlevelex&rev=1557885984

Last update: **2019/05/15 11:06**