

<b>BS2_SetGlobalAPBViolationByDoorOpenHandler</b>	.....	1
.....	.....	1
.....	.....	1
.....	.....	1
.....	.....	2

## [Zone Control API](#) > [BS2\\_SetGlobalAPBViolationByDoorOpenHandler](#)

## **BS2\_SetGlobalAPBViolationByDoorOpenHandler**

```
[ + 2.7.0]           가
                  Global APB      BS2_SetCheckGlobalAPBViolationHandler가
                               가
Global APB By Door Open , 2
1           가 ,          OnCheckGlobalAPBViolationByDoorOpen
2           ,           가
OnUpdateGlobalAPBViolationByDoorOpen .
OnUpdateGlobalAPBViolationByDoorOpen update
```

```
#include "BS_API.h"

int BS2_SetGlobalAPBViolationByDoorOpenHandler(void* context,
OnCheckGlobalAPBViolationByDoorOpen ptrCheck,
OnUpdateGlobalAPBViolationByDoorOpen ptrUpdate);
```

**OnCheckGlobalAPBViolationByDoorOpen**  
**OnUpdateGlobalAPBViolationByDoorOpen**

- [In] *context* : Context
  - [In] *ptrCheck* :
  - [In] *ptrUpdate* :

BS2AuthConfig useGlobalAPB가 true ,  
BS2DoorSensor appUseDoorSensor가 true

BS SDK SUCCESS , 가

## BS2\_CheckGlobalAPBViolationByDoorOpen

From:

<http://kb.supremainc.com/bs2sdk./> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk./doku.php?id=ko:bs2\\_setglobalapbviolationbydooropenhandler](http://kb.supremainc.com/bs2sdk./doku.php?id=ko:bs2_setglobalapbviolationbydooropenhandler)

Last update: **2020/07/21 20:32**