

Table of Contents

BS2_GetUserDatasExFromDirWithKey	1
Declaration	1
파라미터	1
Return value	2
Watch Together	2

BS2_GetUserDatasExFromDirWithKey

[+2.8.2] Gets the user information corresponding to the user identifier from the data extracted by USB.

Declaration

```
#include "BS_API.h"

int BS2_GetUserDatasExFromDirWithKey(void* context, const char* szDir, char*
uids, uint32_t uidCount, BS2UserBlobEx* userBlob, BS2_USER_MASK userMask,
const BS2EncryptKey* key);
```

[View the structure of the BS2UserBlobEx](#)

파라미터

- [In] *context* : Context
- [In] *szDir* : Data storage path
- [In] *uids* : List of user identifiers to be imported
- [In] *uidCount* : Number of user identifiers
- [Out] *userBlob* : Pointer to store user information
- [In] *userMask* : User's Mask
- [In] *key* : Encryption key and the key value specified by [BS2_SetDataEncryptKey](#)

value	description
0x0000	User Identifier
0x0001	User data
0x0002	User Settings
0x0004	User Name
0x0008	Image
0x0010	PIN
0x0020	Card
0x0040	Fingerprint
0x0080	Face
0x0100	Access group
0x0200	Work code
0x0400	Private Message
0x0800	Face(FaceStation F2)

value	description
0x1000	User Settings (FaceStation F2)
0xFFFF	User Information Full

Return value

Returns BS_SDK_SUCCESS if performed successfully, or a corresponding error code if an error occurs.

Watch Together

[BS2_GetUserDatabaseInfoFromDirWithKey](#)

[BS2_GetUserListFromDirWithKey](#)

[BS2_GetUserInfosFromDirWithKey](#)

[BS2_GetUserDatasFromDirWithKey](#)

[BS2_GetUserInfosExFromDirWithKey](#)

[BS2_GetLogFromDirWithKey](#)

[BS2_GetLogBlobFromDirWithKey](#)

[BS2_GetFilteredLogFromDirWithKey](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_getuserdatasexfromdirwithkey&rev=1650247856

Last update: **2022/04/18 11:10**