

## Table of Contents

<b><i>BS2_SetInputConfigEx</i></b> .....	1
API .....	1
Parameters .....	1
Return Values .....	1

 **This page is not fully translated, yet. Please help completing the translation.**  
(remove this paragraph once the translation is finished)

Configuration API > [BS2\\_SetInputConfigEx](#)

## BS2\_SetInputConfigEx

[+ 2.8.1] IM-120 Saves Input Expandable Settings.

### API

```
#include "BS_API.h"

int BS2_SetInputConfigEx(void* context, uint32_t deviceId, const
BS2InputConfigEx* config);
```

[View [configuration api#BS2InputConfigEx|BS2InputConfigEx Structure]]

### Parameters

- [In] *context* : Context
- [In] *deviceId* : Device Identifier
- [In] *config* : Input Expanded Setting Information Pointer

### Return Values

Return BS\_SDK\_SUCCESS when successful, and return an appropriate error code when an error occurs.

From:  
<http://kb.supremainc.com/bs2sdk> - **BioStar 2 Device SDK**

Permanent link:  
[http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_setinputconfigex&rev=1628205252](http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_setinputconfigex&rev=1628205252)

Last update: **2021/08/06 08:14**