

Table of Contents

BS2_SetIPv6ConfigViaUDPEx	1
Declaration	1
Parameter	1
Return Value	1

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

Configuration API > [BS2_SetIPV6ConfigViaUDPEx](#)

BS2_SetIPV6ConfigViaUDPEx

[+ 2.6.3] Stores IPv6 configuration through UDP broadcast with host IP.
It is useful on systems with multiple Ethernet cards installed.

Declaration

```
#include "BS_API.h"

int BS2_SetIPV6ConfigViaUDPEx(void* context, uint32_t deviceId, const
BS2IPV6Config* config, const char* hostipAddr);
```

[See BS2IPV6Config Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : IP configuration pointer
- [In] *hostipAddr* : Host IP address

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_setipv6configviaudpex&rev=1560832110

Last update: **2019/06/18 13:28**