

Table of Contents

Fingerprint API	1
Structure	1
BS2Fingerprint	1

Fingerprint API

API that provides functions to scan, extract, and compare fingerprint template data.

- [BS2_ScanFingerprint](#): Scans a fingerprint from a device and extracts template data.
- [BS2_ScanFingerprintEx](#): Scans a fingerprint from a device and extracts template data and scan image scores.
- [BS2_VerifyFingerprint](#): Compares the template data to check if it is the same finger.
- [BS2_GetLastFingerprintImage](#): Extracts the image of the last scanned fingerprint using the [BS2_ScanFingerprint](#) API.
- [BS2_GetFingerTemplateQuality](#): Checks the quality score of the fingerprint from the fingerprint template data.

Structure

BS2Fingerprint

```
typedef struct {  
    uint8_t index;  
    uint8_t flag;  
    uint8_t reserved[2];  
    uint8_t data[BS2_TEMPLATE_PER_FINGER][BS2_FINGER_TEMPLATE_SIZE];  
} BS2Fingerprint;
```

1. *index*

The index of finger. This is a flag that user can manage manually, not changing automatically. If you want to manage fingerprint index, please assign a number when you enroll fingerprint.

2. *flag*

Flag that indicates the purpose of the fingerprint.


Value	Description
0	Normal fingerprint
1	Duress fingerprint

3. *reserved*

Reserved space.

4. *data*

The data of fingerprint template.



From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:fingerprint_api

Last update: **2019/05/17 11:21**