

Table of Contents

Version 2.7.1 (V2.7.1.0)	1
Date	1
New Features	1
Modified Features	2

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

Version 2.7.1 (V2.7.1.0)

Date

2020-08-21

New Features

- Supports FaceStation F2
- Supports Thermal camera - Facial temperature & Mask detection features

1. FaceStation F2 is supported, user related structures & API are added.

- Structure [BS2UserSettingEx](#) has been added
- Structure [BS2TemplateEx](#) has been added
- Structure [BS2FaceEx](#) has been added
- Structure [BS2UserFaceExBlob](#) has been added
- API [BS2_ScanFaceEx](#) has been added
- API [BS2_ExtractTemplateFaceEx](#) has been added
- API [BS2_EnrollUserFaceEx](#) has been added
- API [BS2_GetUserInfosFaceEx](#) has been added
- API [BS2_GetUserDatasFaceEx](#) has been added

2. Several authentication modes for FaceStation F2 have been added, and you can configure with API and structure below.

- Structure [BS2AuthConfigExt](#) has been added
- API [BS2_GetAuthConfigExt](#) has been added
- API [BS2_SetAuthConfigExt](#) has been added

3. You can extract template by jpg image from FaceStation F2. The template file can be stored on AoC.

- Structure [BS2SmartCardHeader](#) has been added
- API [BS2_ExtractTemplateFaceEx](#) has been added

4. Thermal camera - Facial temperature & Mask detection can be configured with API & structure below.

- Structure [BS2FaceConfigExt](#) has been added
- API [BS2_GetFaceConfigExt](#) has been added
- API [BS2_SetFaceConfigExt](#) has been added

5. Thermal camera information structure and configurable API are available.

- Structure [BS2ThermalCameraConfig](#) has been added
- API [BS2_GetThermalCameraConfig](#) has been added
- API [BS2_SetThermalCameraConfig](#) has been added

6. New event log structure & API to support temperature information have been added.

- Callback function [OnLogReceivedEx](#) has been added
- Structure [BS2EventSmallBlobEx](#) has been added
- API [BS2_StartMonitoringLogEx](#) has been added
- API [BS2_GetLogSmallBlobEx](#) has been added
- API [BS2_GetLogSmallBlobExFromDir](#) has been added

Modified Features

1. A structure is modified to support FaceStation F2's configuration.

- Structure [BS2FaceConfig](#) has been added

2. Masking information of some API retrieving user information with userMask has been added. (Refer to userMask parameter for each API)

- API [BS2_GetUserDatas](#) has been added
- API [BS2_GetUserDatasEx](#) has been added
- API [BS2_GetSupportedUserMask](#) has been added
- API [BS2_GetUserSmallDatas](#) has been added
- API [BS2_GetUserSmallDatasEx](#) has been added
- API [BS2_GetUserDatasFromDir](#) has been added
- API [BS2_GetUserDatasExFromDir](#) has been added
- API [BS2_GetUserSmallDatasFromDir](#) has been added
- API [BS2_GetUserSmallDatasExFromDir](#) has been added
- API [BS2_GetUserInfosFaceEx](#) has been added
- API [BS2_GetUserDatasFaceEx](#) has been added

3. In the past, parameters like fingerSupported, faceSupported were used meaning fingerprint authentication(matching) or facial authentication(matching).

This was confusing because FaceStation2 or returned fingerSupported = true.

From 2.7.1, additional information fingerScanSupported and faceScanSupported is supported to provide more accurate information.

With this, FaceStation2 returns fingerScanSupported = false.

- API [BS2_GetDeviceInfoEx](#) has been added
- Structure [BS2SimpleDeviceInfoEx](#) has been added

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=en:release_note_271&rev=1598231529

Last update: **2020/08/24 10:12**