

Table of Contents

Version 2.8.3 (V2.8.3.2)	1
Date	1
New Features	1
Modified Features	1

Version 2.8.3 (V2.8.3.2)

Date

2022-10-05

New Features

- BioStation 3 connection support (Device name: BS3-DB, BS3-APWB)
- Add User Information Partial Renewal Function.
- Add User statistics acquisition Function.
- Add file log function for debugging that allows file segmentation and storage.

1. BioStation 3 Added connection support, related extended VoIP settings, and RTSP settings.

- Add structure [BS2VoipConfigExt](#)
- Add API [BS2_GetVoipConfigExt](#)
- Add API [BS2_SetVoipConfigExt](#)
- Add structure [BS2RtspConfig](#)
- Add API [BS2_GetRtspConfig](#)
- Add API [BS2_SetRtspConfig](#)

2. Added function to partially update user information.

- Add API [BS2_PartialUpdateUser](#)
- Add API [BS2_PartialUpdateUserEx](#)
- Add API [BS2_PartialUpdateUserSmall](#)
- Add API [BS2_PartialUpdateUserSmallEx](#)
- Add API [BS2_PartialUpdateUserFaceEx](#)

3. Added functionality to get user statistics held by the device.

- Add structure [BS2UserStatistic](#)
- Add API [BS2_GetUserStatistic](#)

4. Added file log function for debugging that allows file segmentation to be saved.

- Add API [BS2_SetDebugFileLogEx](#)

Modified Features

1. When outputting log files for debugging, the time information displayed has been modified to display up to milliseconds.

- Refer to API [BS2_SetDebugFileLog](#)

2. The face setting method changes.

In the face detection stage, face width, which represents the width of the face image, search range, which represents the search range, are entered in pixels.

This was a rather difficult input unit for the user to set up.

The detection distance, wide search provided afterward is changed to a more sensible setting unit by entering the distance to the detected face in cm.

As of the time SDK V2.8.3 is distributed, only 'BioStation 3' can be distance-based, and then extended to 'FaceStation F2' is planned.

- Refer to structure [BS2FaceConfig](#)

3. Added information such as user update support, simulated unlock support, RTSP support, Visual QR support, and extension number registered in Extended VoIP.

- Refer to structure [BS2DeviceCapabilities](#)

4. In the user structure, an infoMask has been added to indicate what credential information the user has.

Also, by modifying the mask value of the infoMask and lowering it to the device, it is possible to change/delete the information that the user has partially.

- Refer to API [BS2User](#)

5. The problem of not applying conditions such as start index and request quantity when obtaining the log of USB has been corrected.

We also fixed an issue that occurs when the acquired log time is abnormally large.

- Refer to API [BS2_GetLogFromDir](#)
- Refer to API [BS2_GetLogBlobFromDir](#)
- Refer to API [BS2_GetLogSmallBlobFromDir](#)
- Refer to API [BS2_GetLogSmallBlobExFromDir](#)
- Refer to API [BS2_GetLogFromDirWithKey](#)
- Refer to API [BS2_GetLogBlobFromDirWithKey](#)
- Refer to API [BS2_GetLogSmallBlobFromDirWithKey](#)
- Refer to API [BS2_GetLogSmallBlobExFromDirWithKey](#)

6. When using the filtered log of USB, the problem of date search not being successful has been corrected.

- Refer to API [BS2_GetFilteredLogFromDir](#)
- Refer to API [BS2_GetFilteredLogFromDirWithKey](#)

7. A simple bug in the C# example has been fixed.

8. Improved usability of SSL at low speed network environments.

9. Fixed the bug that crashed if the access group existed during a USB import.
10. Edited to stabilize code internally in SDK.

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=en:release_note_283

Last update: **2024/10/14 08:51**