BS2_GetFilteredLogFromDirWithKey

USB Exported Control API > BS2_GetFilteredLogFromDirWithKey

BS2_GetFilteredLogFromDirWithKey

[+2.8.2] USB　　　　　Data　　　　　　　　　　　　　　　　　　　　　　　.

```
#include "BS_API.h"

int BS2_GetFilteredLogFromDirWithKey(void* context, const char* szDir, char*
uid, BS2_EVENT_CODE eventCode, BS2_TIMESTAMP start, BS2_TIMESTAMP end,
uint8_t tnakey, BS2Event** logsObj, uint32_t* numLog, const BS2EncryptKey*
key);
```

> BS2Event

- [In] *context* : Context
- [In] *szDir* : Data
- [In] *uid* :　　　　　　　　　NULL　　　　　　　　　　　　　.
- [In] *eventCode* :　　　　　　　　　　O　　　　　　　　　　　　　.
- [In] *start* :　　　　　　　　　　　O　　　　　　　　　　　　　.
- [In] *end* :　　　　　　　　　　O　　　　　　　　　　　　　　.
- [In] *tnakey* : TNA key　　O　　　　　　TNA key　　　　　　.
- [Out] *logsObj* :
- [Out] *numLog* :
- [In] *key* :　　　　　　　　BS2_SetDataEncryptKey　　　　　　　　　.

> logsObj　　　　　　　BS2_ReleaseObject
>
> 　　　　　　　　　.

　　　　　　　　　　BS_SDK_SUCCESS　　　　　　, 　
　.

BS2_GetUserDatabaseInfoFromDirWithKey
BS2_GetUserListFromDirWithKey
BS2_GetUserInfosFromDirWithKey
BS2_GetUserDatasFromDirWithKey
BS2_GetUserInfosExFromDirWithKey
BS2_GetUserDatasExFromDirWithKey
BS2_GetLogFromDirWithKey
BS2_GetLogBlobFromDirWithKey

From:
http://kb.supremainc.com/bs2sdk/ - **BioStar Device SDK**

Permanent link:
http://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_getfilteredlogfromdirwithkey

Last update: **2022/04/12 15:31**