

Communication API	1
.....	1

Communication API

API

LAN, USB, RS485

BS2_SetDeviceEventListener

- **BS2_SetDeviceEventListener**: , Event listener
- **BS2_SearchDevices**: Subnet
- **BS2_SearchDevicesEx**: IP
- **BS2_GetDevices**: 가
- **BS2_ConnectDevice**:
- **BS2_ConnectDeviceIPv6**: IPv6
- **BS2_ConnectDeviceViaIP**: IP Port
- **BS2_DisconnectDevice**:
- **BS2_SetKeepAliveTimeout**: Keep-alive timeout
- **BS2_SetNotificationListener**: Notification listener
- **BS2_SetServerPort**: Server Port
- **BS2_SetSSLServerPort**: Server SSL Port
- **BS2_GetServerPort**: [+ 2.6.3] Server Port
- **BS2_GetSSLServerPort**: [+ 2.6.3] Server SSL Port
- **BS2_IsConnected**:
- **BS2_IsAutoConnection**:
- **BS2_SetAutoConnection**:
- **BS2_GetEnableIPv4**: [+ 2.6.3] IP V4
- **BS2_SetEnableIPv4**: [+ 2.6.3] IP V4
- **BS2_GetEnableIPv6**: [+ 2.6.3] IP V6
- **BS2_SetEnableIPv6**: [+ 2.6.3] IP V6
- **BS2_SetServerPortIPv6**: [+ 2.6.3] IP V6 port
- **BS2_GetServerPortIPv6**: [+ 2.6.3] IP V6 port
- **BS2_SetSSLServerPortIPv6**: [+ 2.6.3] IP V6 ssl port
- **BS2_GetSSLServerPortIPv6**: [+ 2.6.3] IP V6 ssl port
- **BS2_SetDefaultResponseTimeout**: [+ 2.6.3]
- **BS2_GetDefaultResponseTimeout**: [+ 2.6.3]
- **BS2_GetSocketRetryCount**: [+ 2.9.1] Non SSL , /
가
- **BS2_SetSocketRetryCount**: [+ 2.9.1] Non SSL , /
- **BS2_GetSocketSSLRetryCount**: [+ 2.9.1] SSL , / ,
가
- **BS2_SetSocketSSLRetryCount**: [+ 2.9.1] SSL , / ,

```
typedef void (*OnDeviceFound)(uint32_t deviceId);
typedef void (*OnDeviceAccepted)(BS2_DEVICE_ID deviceId);
typedef void (*OnDeviceConnected)(uint32_t deviceId);
```

```
typedef void (*OnDeviceDisconnected)(uint32_t deviceId);
typedef void (*OnAlarmFired)(BS2_DEVICE_ID deviceId, const BS2Event* event);
typedef void (*OnInputDetected)(BS2_DEVICE_ID deviceId, const BS2Event* event);
typedef void (*OnConfigChanged)(BS2_DEVICE_ID deviceId, uint32_t configMask);
```

1. *OnDeviceFound*

Subnet BioStar .

2. *OnDeviceAccepted*

BioStar 가 BioStar .

3. *OnDeviceConnected*

BioStar .

4. *OnDeviceDisconnected*

BioStar .

5. *OnAlarmFired*

Zone .

6. *OnInputDetected*

가 .

7. *OnConfigChanged*

Configuration .

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=ko:communication_api&rev=1676353757

Last update: **2023/02/14 14:49**