

# Table of Contents

E .....	1
---------	---

# A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

---

## E

- **EER (Equal Error Rate)**: As an indicator of Biometric Performance, an ERR(Equal Error Rate) is a point where **FAR (False Acceptance Rate)** and **FRR (False Rejection Rate)** intersects. A device with lower EER is regarded to be more accurate.
- **Encryption**: The act of transforming information so that it is impossible to recognize its original meaning. Storing or transferring information in encrypted form is a way of protecting the information.
- **Enrollment**: A series of steps used to record the biometric information of users in a biometrics system. It involves sampling, template creation, storing, etc.
- **Entrance Limit Zone**: A zone that restricts access at specific times. This zone can be configured in such a way as to restrict the authentication or the authentication count.
- **Epoxy potted**: A material that protects the circuitry by preventing rainwater from entering the device if the device is installed outdoors.
- **Event**: An interaction between a user, the device, and the door. Events are recorded in a log on the BioStar server. They include authentication successes and failures and changes to the status of the door, alarms, etc.
- **Exit button**: A button used to open the **door**. Pressing this button opens the door. The button can be used for doors and zones that do not require separate authentication.
- **Export**: An operation performed by a program that uses a particular data format. It is the act of storing data in a format that is compatible with other programs.

From:  
<http://kb.supremainc.com/knowledge/> -

Permanent link:  
[http://kb.supremainc.com/knowledge/doku.php?id=en:e\\_e&rev=1547007950](http://kb.supremainc.com/knowledge/doku.php?id=en:e_e&rev=1547007950)

Last update: **2019/01/09 13:25**