

# Table of Contents

M .....	1
---------	---

# A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

---

## M

- **Master device:** Among the devices that are connected through [RS-485](#), the device that plays the role of a controller. It processes data by periodically monitoring the [slave device](#). It is also called a host device.
- **Matching timeout:** The time limit given to device matching or server matching. Matching fails if the matching does not get completed within the time limit.
- **Message timeout:** The duration of time a message is displayed when there is no user interaction.
- **Minutiae:** The specific details in the [ridges](#) of a fingerprint used to recognize the fingerprint.
- **Model number:** A generic number given to a [device](#) by the manufacturer in order to identify its type.
- **MSB (Most Significant Bit):** The bit at the highest position of binary data (the left-most bit) or its content. It is the opposite of the [Least Significant Bit \(LSB\)](#).
- **MTU (Maximum Transmission Unit):** The maximum amount of packets that can be transmitted through the network.

From:  
<http://kb.supremainc.com/knowledge/> -

Permanent link:  
[http://kb.supremainc.com/knowledge/doku.php?id=en:e\\_m&rev=1467955202](http://kb.supremainc.com/knowledge/doku.php?id=en:e_m&rev=1467955202)

Last update: **2016/07/08 14:20**