

Table of Contents

M 1

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

M

- **Man-trap**: A physical access control system for preventing unauthorized access and separating security zones from non-security zones.
- **Master device**: Among the devices that are connected through **RS-485**, the device that plays the role of a controller. It processes data by periodically monitoring the **slave device**. It is also called a host device.
- **Matching timeout**: The time limit given to device matching or server matching. Matching fails if the matching does not get completed within the time limit.
- **Message timeout**: The duration of time a message is displayed when there is no user interaction.
- **Minutiae**: The specific details in the **ridges** of a fingerprint used to recognize the fingerprint.
- **Model number**: A generic number given to a **device** by the manufacturer in order to identify its type.
- **MSB (Most Significant Bit)**: The bit at the highest position of binary data (the left-most bit) or its content. It is the opposite of the **Least Significant Bit (LSB)**.
- **MTU (Maximum Transmission Unit)**: The maximum amount of packets that can be transmitted through the network.
- **Muster Zone**: A zone designated for the gathering of members in case of an emergency such as a fire. This is used to monitor the number and roster of personnel in a certain zone, and to notify administrators via an alarm or alert if a user has remained in a particular zone for a certain period of time.

From:
<http://kb.supremainc.com/knowledge/> -

Permanent link:
http://kb.supremainc.com/knowledge/doku.php?id=en:e_m&rev=1546411589

Last update: **2019/01/02 15:46**