

Table of Contents

- BS2_RemoveWiegandDevices*** 1
- Declaration 1
- Parameter 1
- Return Value 1
- See Also 1

[Wiegand API](#) > [BS2_RemoveWiegandDevices](#)

BS2_RemoveWiegandDevices

Removes Wiegand card readers.

Declaration

```
#include "BS_API.h"

int BS2_RemoveWiegandDevices(void* context, uint32_t deviceId, uint32_t**
wiegandDevice, uint32_t* numWiegandDevice);
```

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *wiegandDevice* : List of Wiegand card readers to remove
- [In] *numWiegandDevice* : Number of Wiegand card readers to remove

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_SearchWiegandDevices](#)

[BS2_GetWiegandDevices](#)

[BS2_AddWiegandDevices](#)

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_removewieganddevices

Last update: **2017/03/01 17:20**