

# Table of Contents

<b>BS2_ResetConfigExceptNetInfo</b> .....	1
Declaration .....	1
Paramter .....	1
Return Value .....	1

## BS2\_ResetConfigExceptNetInfo

[+ V2.6.0] Initializes the setting information of the device. (Excluding network settings)  
Supported in the following versions or higher.

Model	Ver.
BS2	V1.6.0
BSA2	V1.5.0
CS-40	V1.1.0
BEP2	V1.1.0
BSL2	V1.3.0
BEW2	V1.2.0
BLN2	V1.0.0
FS2	V1.1.0

### Declaration

```
#include "BS_API.h"

int BS2_ResetConfigExceptNetInfo(void* context, uint32_t deviceId, uint8_t includingDB);
```

### Paramter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *includingDB* : Weather to delete access group, level, schedule, holiday group, door, zone information

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

From:  
<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:  
[http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_resetconfigexceptnetinfo&rev=1619657104](http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_resetconfigexceptnetinfo&rev=1619657104)

Last update: **2021/04/29 09:45**