

BS2_GetAuthOperatorLevelEx

.....

.....

.....

.....

.....

.....

1

1

1

1

2

BS2_GetAuthOperatorLevelEx

[+ 2.6.3]

userIDs가 .

BS2_SetAuthConfig, BS2_GetAuthConfig10 ,

1000 .

BS2_SetAuthConfigBS2_GetAuthConfig가 .

```
#include "BS_API.h"

int BS2_GetAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId,
BS2_USER_ID* userIDs, uint32_t userIDCount, BS2AuthOperatorLevel**
operatorlevelObj, uint32_t* numOperatorlevel);
```

BS2AuthOperatorLevel

- [In] *context* : Context
- [In] *deviceId* :
- [In] *userIDs* : 가
- [In] *userIDCount* :
- [Out] *operatorlevelObj* :
- [Out] *numOperatorlevel* :



BS_SDK_SUCCESS , 가

[BS2_GetAuthOperatorLevelEx](#)
[BS2_GetAllAuthOperatorLevelEx](#)
[BS2_SetAuthOperatorLevelEx](#)
[BS2_RemoveAuthOperatorLevelEx](#)
[BS2_RemoveAllAuthOperatorLevelEx](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_getauthoperatorlevelex&rev=1557885743

Last update: **2019/05/15 11:02**