

BS2_SetAuthOperatorLevelEx

.....

.....

.....

.....

.....

.....

1

1

1

1

2

BS2_SetAuthOperatorLevelEx

[+ 2.6.3] 가 .
BS2_SetAuthConfig, BS2_GetAuthConfig 10 가
, 1000 가 .

BS2AuthConfig

,

1000

가

,

BS2AuthConfig

,

BS2AuthConfig

```
#include "BS_API.h"

int BS2_SetAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId,
BS2AuthOperatorLevel* operatorlevels, uint32_t operatorlevelCount);
```

BS2AuthOperatorLevel

- [In] context : Context
- [In] deviceId :
- [In] operatorlevels : 가
- [In] operatorlevelCount : 가

BS_SDK_SUCCESS , 가

[BS2_GetAuthOperatorLevelEx](#)
[BS2_GetAllAuthOperatorLevelEx](#)
[BS2_SetAuthOperatorLevelEx](#)
[BS2_RemoveAuthOperatorLevelEx](#)
[BS2_RemoveAllAuthOperatorLevelEx](#)

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk./doku.php?id=ko:bs2_setauthoperatorlevelex&rev=1557916892

Last update: **2019/05/15 19:41**