

BS2_SetAuthOperatorLevelEx

.....

.....

.....

.....

.....

.....

1

1

1

2

2

[Device API](#) > [BS2_SetAuthOperatorLevelEx](#)

BS2_SetAuthOperatorLevelEx

[+ 2.6.3] 가 .
[BS2_SetAuthConfig](#), [BS2_GetAuthConfig](#) 10 가
 , 1000 가 .

FW
 BS2 1.8.0, A2 1.7.0, L2 1.5.0, N2 1.2.0, FS 1.3.0, FaceLite 1.0.1, CS40 1.3.0, P2 1.3.0, W2 1.4.0, Xpass
 2 1.0.0 + 3Q 2019 2

[BS2AuthConfig](#) , 1000 가
 ,
[BS2AuthConfig](#) .
[BS2AuthConfig](#) .

```
#include "BS_API.h"
```

```
int BS2_SetAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId,  
BS2AuthOperatorLevel* operatorlevels, uint32_t operatorlevelCount);
```

[BS2AuthOperatorLevel](#)

- [In] *context* : Context
- [In] *deviceId* :
- [In] *operatorlevels* : 가
- [In] *operatorlevelCount* : 가

BS_SDK_SUCCESS , 가

[BS2_GetAuthOperatorLevelEx](#)
[BS2_GetAllAuthOperatorLevelEx](#)
[BS2_SetAuthOperatorLevelEx](#)
[BS2_RemoveAuthOperatorLevelEx](#)
[BS2_RemoveAllAuthOperatorLevelEx](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_setauthoperatorlevelex&rev=1610432780

Last update: **2021/01/12 15:26**