

2.9.8 **(v2.9.8.0)** 1
 1
 1
 2

2.9.8 (v2.9.8.0)

2024-9-30

- ID,
- BioStation 3 IP SIP
- BioStation 3 IP , RTSP
- 가
- X-Station 2 PIN 가 가
- RS-485 가
- CoreStation Aux Input 가

1. ID 가

- [BS2DisplayConfig](#) - authMsgUserName, authMsgUserID

2. BioStation 3 IP UDP, TCP, TLS 가

- [BS2VoipConfigExt](#) - transport (: BioStation 3)

3. BioStation 3 IP RTSP 가

- [BS2VoipConfigExt](#) - resolution (: BioStation 3)
- [BS2RtspConfig](#) - resolution (: BioStation 3, BioEntry W3)

4. 가

BioStation 3, FaceStation F2, BioEntry W3

- [BS2FaceConfigExt](#) - maskCheckMode
- [BS2DeviceCapabilities](#) - authDenyMaskSupported

5. X-Station 2 PIN 가

- [BS2DisplayConfig](#) - scrambleKeyboardMode
- [BS2DeviceCapabilities](#) - scrambleKeyboardModeSupported

6. RS-485 가 .

- [BS2_SetSlaveBaudrate](#) 가

7. CoreStation40 Aux Input 가 .

- [BS2InputConfig](#) - aux

1. C++(x64) BS2_ReleaseContext() 가 .

2. BS2_SetAutoConnection , 가

3. so Linux Library SONAME .

4. BS2_RS485Config, BS2_RS485ConfigEx mode 'Not use'가

5. C#

- ConfigControl `getDeviceCapabilities()`
- UserControl `imagedata` .
- SlaveControl `wiegandDeviceID` .

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=ko:release_note_298

Last update: **2024/10/23 16:29**