

SDK API 1
..... 1
 BS2EncryptKey 1

SDK API

PIN

API

- [BS2_Version](#): SDK
- [BS2_AllocateContext](#): Context
- [BS2_ReleaseContext](#): Context
- [BS2_Initialize](#): Context
- [BS2_ReleaseObject](#):
- [BS2_MakePinCode](#): PIN
- [BS2_SetMaxThreadCount](#):
- [BS2_ComputeCRC16CCITT](#): CRC-16 CCITT
- [BS2_GetCardModel](#): 가
- [BS2_GetCredentialKeyInfo](#): 가
- [BS2_SetCredentialKeyInfo](#):
- [BS2_RemoveCredentialKeyInfo](#):
- [BS2_GetDataEncryptKey](#): 가
- [BS2_SetDataEncryptKey](#):
- [BS2_RemoveDataEncryptKey](#):

BS2EncryptKey

```
enum
{
    BS2_ENC_KEY_SIZE = 32,
};

/**
 * BS2EncryptKey
 */
typedef struct
{
    uint8_t key[BS2_ENC_KEY_SIZE];
    uint8_t reserved[32];
} BS2EncryptKey;
```

1. *key*

2. *reserved*

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=ko:sdk_api&rev=1523513769

Last update: **2018/04/12 15:16**