

<b>SDK API</b> .....	1
.....	1
BS2EncryptKey .....	1

# SDK API

PIN

API

- [BS2\\_Version](#): SDK
- [BS2\\_AllocateContext](#): Context
- [BS2\\_ReleaseContext](#): Context
- [BS2\\_Initialize](#): Context
- [BS2\\_ReleaseObject](#):
- [BS2\\_MakePinCode](#): PIN
- [BS2\\_SetMaxThreadCount](#):
- [BS2\\_ComputeCRC16CCITT](#): CRC-16 CCITT
- [BS2\\_GetCardModel](#): 가
- [BS2\\_GetDataEncryptKey](#): 가
- [BS2\\_SetDataEncryptKey](#):
- [BS2\\_RemoveDataEncryptKey](#):
- [BS2\\_SetDeviceSearchingTimeout](#) :

## BS2EncryptKey

```
enum
{
    BS2_ENC_KEY_SIZE = 32,
};

typedef struct
{
    uint8_t key[BS2_ENC_KEY_SIZE];
    uint8_t reserved[32];
} BS2EncryptKey;
```

1. *key*

2. *reserved*

From: <https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link: [https://kb.supremainc.com/bs2sdk/doku.php?id=ko:sdk\\_api&rev=1537145456](https://kb.supremainc.com/bs2sdk/doku.php?id=ko:sdk_api&rev=1537145456)

Last update: **2018/09/17 09:50**

