

**SDK API** ..... 1  
..... 1  
    BS2EncryptKey ..... 1

# SDK API

- [BS2\\_Version](#): SDK
- [BS2\\_AllocateContext](#): Context
- [BS2\\_ReleaseContext](#): Context
- [BS2\\_Initialize](#): Context
- [BS2\\_ReleaseObject](#):
- [BS2\\_MakePinCode](#): PIN
- [BS2\\_MakePinCodeWithKey](#): PIN . [+ 2.7.1]
- [BS2\\_SetMaxThreadCount](#):
- [BS2\\_ComputeCRC16CCITT](#): CRC-16 CCITT
- [BS2\\_GetCardModel](#): 가
- [BS2\\_GetDataEncryptKey](#): 가
- [BS2\\_SetDataEncryptKey](#): PIN . [+ 2.7.1]
- [BS2\\_RemoveDataEncryptKey](#):
- [BS2\\_SetDeviceSearchingTimeout](#):
- [BS2\\_SetDebugFileLog](#):

## BS2EncryptKey

```
enum
{
    BS2_ENC_KEY_SIZE = 32,
};

typedef struct
{
    uint8_t key[BS2_ENC_KEY_SIZE];
    uint8_t reserved[32];
} BS2EncryptKey;
```

1. *key*

2. *reserved*

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk./doku.php?id=ko:sdk\\_api&rev=1600731996](http://kb.supremainc.com/bs2sdk./doku.php?id=ko:sdk_api&rev=1600731996)

Last update: **2020/09/22 08:46**