

Server API	1
.....	1
OnUserPhrase	2
OnBarcodeScanned	2

Server API

, BioStar

UFMatcher.dll

가

library

ID

ID : sales_id@supremainc.com

- [BS2_SetServerMatchingHandler](#):
- [BS2_VerifyUser](#): User ID
- [BS2_IdentifyUser](#):
- [BS2_VerifyUserEx](#): [+ 2.4.0] User ID
- [BS2_IdentifyUserEx](#): [+ 2.4.0]
- [BS2_VerifyUserSmall](#): [+ 2.6.3] User ID
- [BS2_IdentifyUserSmall](#): [+ 2.6.3]
- [BS2_VerifyUserSmallEx](#): [+ 2.6.3] User ID
- [BS2_IdentifyUserSmallEx](#): [+ 2.6.3]
- [BS2_VerifyUserFaceEx](#): [+ 2.7.2] User ID
- [BS2_SetUserPhraseHandler](#): [+ 2.7.0]
- [BS2_ResponseUserPhrase](#): [+ 2.7.0]
- [BS2_SetBarcodeScanListener](#): [+ 2.8.2] Barcode listener

```
typedef void (*OnVerifyUser)(uint32_t deviceId, uint16_t seq, uint8_t
isCard, uint8_t cardType, const uint8_t* data, uint32_t dataLen);
typedef void (*OnIdentifyUser)(uint32_t deviceId, uint16_t seq, uint8_t
format, const uint8_t* templateData, uint32_t templateSize);
```

1. OnVerifyUser

Card , User ID가

BioStar

2. OnIdentifyUser

OnUserPhrase

```
typedef void (*OnUserPhrase)(uint32_t deviceId, uint16_t seq, const char* userID);
```

1. *deviceId*

2. *seq*

3. *userID*

ID

OnBarcodeScanned

barcode가 scan

```
typedef void (*OnBarcodeScanned)(uint32_t deviceId, const char* barcode);
```

1. *deviceId*

barcode

ID

2. *barcode*

barcode

From:

<https://kb.supremainc.com/bs2sdk/> - BioStar 2 Device SDK

Permanent link:

https://kb.supremainc.com/bs2sdk./doku.php?id=ko:server_api&rev=1649748330

Last update: 2022/04/12 16:25