

User Management API 1

..... 1

BS2User 1

BS2UserSetting 2

BS2UserPhoto 4

BS2UserBlob 4

BS2Job 5

BS2UserBlobEx 5

BS2UserSmallBlob 6

BS2UserSmallBlobEx 7

BS2UserSettingEx 8

BS2UserFaceExBlob 10

User Management API

API

- [BS2_GetUserList](#): ID 가
- [BS2_RemoveUser](#):
- [BS2_RemoveAllUser](#):
- [BS2_GetUserInfos](#): ID 가
- [BS2_GetUserInfosEx](#): [+ 2.4.0] ID 가 . (Job code, User phrase)
- [BS2_EnrollUser](#):
- [BS2_EnrollUserEx](#): [+ 2.4.0] . (Job code, User phrase)
- [BS2_EnrollUser](#): [+ 2.6.3]
- [BS2_EnrollUserEx](#): [+ 2.6.3] . (Job code, User phrase)
- [BS2_GetUserDatas](#): 가
- [BS2_GetUserDatasEx](#): [+ 2.5.0] 가 가 . (Job code, User phrase)
- [BS2_GetSupportedUserMask](#): 가
- [BS2_EnrollUserSmall](#): [+ 2.6.3]
- [BS2_EnrollUserSmallEx](#): [+ 2.6.3]
- [BS2_GetUserSmallInfos](#): [+ 2.6.3] , ID
- [BS2_GetUserSmallInfosEx](#): [+ 2.6.3] , ID
- [BS2_GetUserSmallDatas](#): [+ 2.6.3] ,
- [BS2_GetUserSmallDatasEx](#): [+ 2.6.3] ,
- [BS2_EnrollUserFaceEx](#): [+ 2.7.1] FaceStation F2
- [BS2_GetUserInfosFaceEx](#): [+ 2.7.1] FaceStation F2 ID 가
- [BS2_GetUserDatasFaceEx](#): [+ 2.7.1] FaceStation F2 가

BS2User

```
typedef struct {
    char userID[BS2_USER_ID_SIZE];
    uint8_t formatVersion;
    uint8_t flag;
    uint16_t version;
    uint8_t numCards;
    uint8_t numFingers;
    uint8_t numFaces;
    uint8_t reserved2[1];
    uint32_t authGroupID;
    uint32_t faceChecksum;
}
```

```
} BS2User;
```

1. *userID* , 1 ~ 4294967295 가 .

2. *formatVersion* .

3. *flag* flag OR 가 .

0x00	None
0x01	가
0x02	가
0x04	가
0x80	가

4. *version* .

5. *numCards* .

6. *numFingers* .

7. *numFaces* .

8. *authGroupID* ID.

9. *faceChecksum* .

BS2UserSetting

FaceStation F2

```
typedef struct {
    uint32_t startTime;
    uint32_t endTime;
    uint8_t fingerAuthMode;
    uint8_t cardAuthMode;
    uint8_t idAuthMode;
    uint8_t securityLevel;
} BS2UserSetting;
```

1. *startTime*

가 0

2. *endTime*

가 0

3. *fingerAuthMode*

0	
1	PIN
254	
255	()

4. *cardAuthMode*

2	
3	
4	PIN
5	PIN
6	, , PIN
254	
255	()

5. *idAuthMode*

ID

7	ID
8	ID PIN
9	ID PIN
10	ID PIN
254	
255	()

6. *securityLevel*

0	
1	
2	
3	
4	
5	

BS2UserPhoto

```
typedef struct {
    uint32_t size;
    uint8_t data[BS2_USER_PHOTO_SIZE];
} BS2UserPhoto;
```

1. *size*

2. *data*

16kb

BS2UserBlob

```
typedef struct {
    BS2User user;
    BS2UserSetting setting;
    uint8_t name[BS2_USER_NAME_SIZE];
    BS2UserPhoto photo;
    uint8_t pin[BS2_PIN_HASH_SIZE];
    BS2CSNCard* cardObjs;
    BS2Fingerprint* fingerObjs;
    BS2Face* faceObjs;
    uint32_t accessGroupId[BS2_MAX_NUM_OF_ACCESS_GROUP_PER_USER];
} BS2UserBlob;
```

1. *user*

2. *setting*

3. *name*

UTF-8

4. *photo*

Jpeg

5. *pin*

PIN

BS_MakePinCode

6. *cardObjs*

user.numCards

[Smartcard API](#)

7. *fingerObjs*

user.numFingers

[Fingerprint API](#)

8. *faceObjs*

Face API

user.numFaces9. *accessGroupId*

가

16

BS2Job

```
typedef struct {
    uint8_t numJobs;
    uint8_t reserved[3];

    struct {
        BS2_JOB_CODE code;
        BS2_JOB_LABEL label;
    } jobs[BS2_MAX_JOB_SIZE];
} BS2Job;
```

1. *numJobs*

Job

2. *reserved*3. *jobs*

T&A

Job

BS2UserBlobEx

```
typedef struct {
    BS2User user;
    BS2UserSetting setting;
    uint8_t name[BS2_USER_NAME_SIZE];
    BS2UserPhoto photo;
    uint8_t pin[BS2_PIN_HASH_SIZE];
    BS2CSNCard* cardObjs;
    BS2Fingerprint* fingerObjs;
    BS2Face* faceObjs;
    BS2Job job;
    BS2_USER_PHRASE phrase;
    uint32_t accessGroupId[BS2_MAX_NUM_OF_ACCESS_GROUP_PER_USER];
} BS2UserBlobEx;
```

1. *user*2. *setting*

3. name

UTF-8

4. photo

Jpeg

5. pin

PIN BS_MakePinCode

6. cardObjs

user.numCards

[Smartcard API](#)

7. fingerObjs

user.numFingers

[Fingerprint API](#)

8. faceObjs

user.numFaces

[Face API](#)

9. job

10. phrase

UI (FS2 FW 1.0.0 가)

11. accessGroupId

가 16

BS2UserSmallBlob

```

typedef struct {
    BS2User user;
    BS2UserSetting setting;
    uint8_t name[BS2_USER_NAME_SIZE];
    BS2UserPhoto* photo;
    uint8_t pin[BS2_PIN_HASH_SIZE];
    BS2CSNCard* cardObjs;
    BS2Fingerprint* fingerObjs;
    BS2Face* faceObjs;
    uint32_t accessGroupId[BS2_MAX_NUM_OF_ACCESS_GROUP_PER_USER];
} BS2UserSmallBlob;

```

1. user

2. setting

3. name

UTF-8

4. photo

Jpeg

5. pin

PIN BS_MakePinCode

6. cardObjs

user.numCards

Smartcard API

7. fingerObjs

user.numFingers

Fingerprint API

8. faceObjs

user.numFaces

Face API

9. accessGroupId

가

16

BS2UserSmallBlobEx

```
typedef struct {
    BS2User user;
    BS2UserSetting setting;
    uint8_t name[BS2_USER_NAME_SIZE];
    BS2UserPhoto* photo;
    uint8_t pin[BS2_PIN_HASH_SIZE];
    BS2CSNCard* cardObjs;
    BS2Fingerprint* fingerObjs;
    BS2Face* faceObjs;
    BS2Job job;
    BS2_USER_PHRASE phrase;
    uint32_t accessGroupId[BS2_MAX_NUM_OF_ACCESS_GROUP_PER_USER];
} BS2UserSmallBlobEx;
```

1. user

2. setting

3. name

UTF-8

4. photo

Jpeg

5. *pin*

PIN *BS_MakePinCode*

6. *cardObjs*

user.numCards

Smartcard API

7. *fingerObjs*

user.numFingers

Fingerprint API

8. *faceObjs*

user.numFaces

Face API

9. *job*

10. *phrase*

UI (FS2 FW 1.0.0 가)

11. *accessGroupId*

가 16

BS2UserSettingEx

```
typedef struct {
    uint8_t faceAuthMode;
    uint8_t fingerprintAuthMode;
    uint8_t cardAuthMode;
    uint8_t idAuthMode;
    uint8_t reserved[28];
} BS2UserSettingEx;
```

FaceStation F2

1. *faceAuthMode*

	1	2	3	4
11				
12				
13		PIN		
14		PIN		
15			PIN	
254				

	1	2	3	4
255) (

2. fingerprintAuthMode

	1	2	3	4
16				
17				
18		PIN		
19		PIN		
20			PIN	
254				
255) (

3. cardAuthMode

	1	2	3
21			
22			
23			
24		PIN	
25			
26			PIN
27			PIN
28		PIN	
29			
30			PIN
31			
32			PIN
33			PIN
34			PIN
35			PIN
254			
255) (

4. idAuthMode

ID

	1	2	3
36	ID		
37	ID		
38	ID	PIN	
39	ID		
40	ID	PIN	
41	ID	PIN	
42	ID	PIN	
43	ID		
44	ID		PIN
45	ID		
46	ID		PIN
47	ID		PIN
48	ID		PIN
49	ID		PIN
254			
255) (

5. reserved

BS2UserFaceExBlob

```
typedef struct
{
    BS2User user;
    BS2UserSetting setting;
    BS2_USER_NAME user_name;
    BS2UserPhoto* user_photo_obj;
    BS2_USER_PIN pin;
    BS2CSNCard* cardObjs;
    BS2Fingerprint* fingerObjs;
    BS2Face* faceObjs; // FS2, FL
    BS2Job job;
    BS2_USER_PHRASE phrase;
    BS2_ACCESS_GROUP_ID accessGroupId[BS2_MAX_NUM_OF_ACCESS_GROUP_PER_USER];

    BS2UserSettingEx settingEx; // F2
    BS2FaceEx* faceExObjs; // F2
} BS2UserFaceExBlob;
```

1. user

2. *setting*

3. *name*

UTF-8

4. *photo*

Jpeg

5. *pin*

PIN

BS_MakePinCode

6. *cardObjs*

user.numCards

[Smartcard API](#)

7. *fingerObjs*

user.numFingers

[Fingerprint API](#)

8. *faceObjs*

FaceStation2, FaceLite

user.numFaces

[Face API](#)

9. *job*

10. *phrase*

UI

(FS2 FW 1.0.0

가)

11. *accessGroupId*

가

16

12. *settingEx*

FaceStation F2

가

13. *faceExObjs*

FaceStation F2

user.numFaces

[Face API](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk./doku.php?id=ko:user_management_api&rev=1606379777

Last update: **2020/11/26 17:36**