

Table of Contents

<i>BS2_VerifyUserSmall</i>	1
Declaration	1
Parameter	1
Return Value	1
See Also	2

Server API > BS2_VerifyUserSmall

BS2_VerifyUserSmall

[+ 2.6.3] Transfers user information mapped to the card or user ID authentication results to the device.

The only difference between [BS2_VerifyUser](#) which is using structure [BS2UserBlob](#) is that the 5th parameter BS2UserPhoto of BS2UserSmallBlob is using pointer for efficient memory use.

Declaration

```
#include "BS_API.h"

int BS2_VerifyUserSmall(void* context, uint32_t deviceId, uint16_t seq, int
handleResult, BS2UserSmallBlob* userBlob);
```

[See BS2UserSmallBlob Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence number
- [In] *handleResult* : Value of matching result(BS_SDK_SUCCESS or BS_SDK_ERROR_XXX)
- [In] *userBlob* : Matched user information

NOTE

Packet sequence number must be equivalent to the value sent from the OnVerifyUser.

If the handleResult is BS_SDK_SUCCESS, the userBlob should not be null.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

See Also

[BS2_VerifyUserSmall](#)
[BS2_IdentifyUserSmall](#)
[BS2_VerifyUserSmallEx](#)
[BS2_IdentifyUserSmallEx](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_verifyusersmall

Last update: **2019/06/18 16:29**