

# Table of Contents

**Fingerprint API**

**Structure**

BS2Fingerprint

.....

.....

.....

1

1

1

# Fingerprint API

API that provides functions to scan, extract, and compare fingerprint template data.

- [BS2\\_ScanFingerprint](#): Scans a fingerprint from a device and extracts template data.
- [BS2\\_VerifyFingerprint](#): Compares the template data to check if it is the same finger.
- [BS2\\_GetLastFingerprintImage](#): Extracts the image of the last scanned fingerprint using the [BS2\\_ScanFingerprint](#) API.

## Structure

### BS2Fingerprint

```
typedef struct {  
    uint8_t index;  
    uint8_t flag;  
    uint8_t reserved[2];  
    uint8_t data[BS2_TEMPLATE_PER_FINGER][BS2_FINGER_TEMPLATE_SIZE];  
} BS2Fingerprint;
```

#### 1. *index*

The index of finger.

#### 2. *flag*

Flag that indicates the purpose of the fingerprint.

Value	Description
0	Normal fingerprint
1	Duress fingerprint

#### 3. *reserved*

Reserved space.

#### 4. *data*

The data of fingerprint template.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk/doku.php?id=en:fingerprint\\_api&rev=1469769934](http://kb.supremainc.com/bs2sdk/doku.php?id=en:fingerprint_api&rev=1469769934)

Last update: **2016/07/29 14:25**