

Table of Contents

<i>BS2_ClearDeviceZoneAccessRecord</i>	1
Declaration	1
Parameter	1
Return Value	1
See Also	1

[Zone Control API](#) > [BS2_ClearDeviceZoneAccessRecord](#)

BS2_ClearDeviceZoneAccessRecord

Updates selected users to be not violating against the Ethernet zone rule.

Declaration

```
#include "BS_API.h"

int BS2_ClearDeviceZoneAccessRecord(void* context, uint32_t deviceId,
uint32_t zoneID, char* uids, uint32_t uidCount);
```

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *zoneID* : Zone ID
- [In] *uids* : List of user IDs to update
- [In] *uidCount* : Number of user IDs

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.
If there is an error, the corresponding error code will be returned.

See Also

[BS2_GetDeviceZone](#)
[BS2_GetAllDeviceZone](#)
[BS2_SetDeviceZone](#)
[BS2_RemoveDeviceZone](#)
[BS2_SetAntiPassbackZone](#)
[BS2_RemoveAllDeviceZone](#)
[BS2_SetDeviceZoneAlarm](#)
[BS2_ClearAllDeviceZoneAccessRecord](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_cleardevicezoneaccessrecord&ev=1504602170

Last update: **2017/09/05 18:02**