

# Table of Contents

<b>BS2_GetDefaultResponseTimeout</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

[Communication API](#) > [BS2\\_GetDefaultResponseTimeout](#)

---

## BS2\_GetDefaultResponseTimeout

[+ 2.6.3] Gets default response timeout between device and server. Default is set as 10sec. It defines timeout of API except some APIs such as connection(hardcoded 3s), BS2\_UpdateResource and BS2\_GetFilteredLog(300s).

### Declaration

```
#include "BS_API.h"

int BS2_GetDefaultResponseTimeout(void* context, long* poMs);
```

### Parameter

- [In] *context* : Context
- [Out] *poMs* : Respond waiting time (milli seconds)

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_SetDefaultResponseTimeout](#)

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[https://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2\\_getdefaultresponsetimeout](https://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_getdefaultresponsetimeout)

Last update: **2019/07/09 14:05**