


Table of Contents

BS2_GetLogSmallBlob	1
Declaration	1
Parameter	1
Return Value	1
See Also	2

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.
(remove this paragraph once the translation is finished)

[Log Management API](#) > [BS2_GetLogSmallBlob](#)

BS2_GetLogSmallBlob

[+ 2.6.4] Retrieves logs filtered by EventMask from the device.
The difference from [BS2_GetLogBlob](#) which is using [BS2EventBlob](#) is that the parameter imageObj in BS2EventSmallBlob is changed to pointer for memory efficiency.
Except this, everything is the same. 니다.

Declaration

```
#include "BS_API.h"

int BS2_GetLogSmallBlob(void* context, uint32_t deviceId, uint16_t
eventMask, uint32_t eventId, uint32_t amount, BS2EventSmallBlob** logsObj,
uint32_t* numLog);
```

[See BS2EventSmallBlob Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *eventMask* : event mask
- [In] *eventId* : Log record ID, retrieves from the first record if it is 0
- [In] *amount* : log amount, retrieves all after eventID if it is 0
- [Out] *logsObj* : Pointer of storing the log record address
- [Out] *numLog* : The number of log records

NOTE

The logsObj variable needs to return the memory to the system by the [BS2_ReleaseObject](#) function after being used.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_GetLog](#)

[BS2_GetFilteredLog](#)

[BS2_ClearLog](#)

[BS2_GetLogBlob](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_getlogsmallblob&rev=1581990896

Last update: **2020/02/18 10:54**