

Table of Contents

BS2_GetLogSmallBlobFromDir	1
Declaration	1
Parameter	1
Return Value	1
See Also	2

BS2_GetLogSmallBlobFromDir

[+ 2.6.4] Retrieves logs filtered by EventMask from the USB exported data. The difference from [BS2_GetLogBlobFromDir](#) which is using [BS2EventBlob](#) is that the parameter imageObj in BS2EventSmallBlob is changed to pointer for memory efficiency. Except this, everything is the same.

Declaration

```
#include "BS_API.h"

int BS2_GetLogSmallBlobFromDir(void* context, const char* szDir, uint16_t
eventMask, BS2_EVENT_ID eventId, uint32_t amount, BS2EventSmallBlob**
logsObj, uint32_t* numLog);
```

[BS2EventSmallBlob구조체 보기](#)

Parameter

- [In] *context* : Context
- [In] *szDir* : Data storage path
- [In] *eventMask* : event mask
- [In] *eventId* : Log record ID, retrieves from the first record if it is 0
- [In] *amount* : Maximum log amount, retrieves all after eventId if it is 0
- [Out] *logsObj* : Pointer of storing the log record address
- [Out] *numLog* : The number of log records

NOTE

The logsObj variable needs to return the memory to the system by the [BS2_ReleaseObject](#) function after being used.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.
If there is an error, the corresponding error code will be returned.

See Also

[BS2_AllocateUsbContext](#)
[BS2_ReleaseUsbContext](#)
[BS2_GetUserDatabaseInfoFromDir](#)
[BS2_GetUserListFromDir](#)
[BS2_GetUserInfosFromDir](#)
[BS2_GetUserDatasFromDir](#)
[BS2_GetUserInfosExFromDir](#)
[BS2_GetUserDatasExFromDir](#)
[BS2_GetLogFromDir](#)
[BS2_GetFilteredLogFromDir](#)
[BS2_GetLogBlobFromDir](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_getlogsmallblobfromdir&rev=1581989669

Last update: **2020/02/18 10:34**