Table of Contents

User Management API > BS2_GetUserSmallInfosEx

BS2_GetUserSmallInfosEx

[+ 2.6.3] Gets the user information of the given user ID with efficient use of memory.
The only difference between BS2_GetUserInfosEx which is using structure BS2UserBlob is that the 3rd parameter BS2UserPhoto of BS2UserSmallBlobEx is using pointer for efficient memory use.

Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosEx(void* context, uint32_t deviceId, char* uids,
uint32_t uidCount, BS2UserSmallBlobEx* userBlob);
```

> See BS2UserSmallBlobEx Structure

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *uids* : User ID list trying to get
- [In] *uidCount* : Number of user ID
- [Out] *userBlob* : Pointer to store the user information

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.
If there is an error, the corresponding error code will be returned.

See Also

BS2_EnrollUserSmall
BS2_EnrollUserSmallEx
BS2_GetUserSmallInfos
BS2_GetUserSmallInfosEx
BS2_GetUserSmallDatas
BS2_GetUserSmallDatasEx

From:
http://kb.supremainc.com/bs2sdk./ - **BioStar 2 Device SDK**

Permanent link:
http://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_getusersmallinfosex

Last update: **2019/06/18 16:32**