

# Table of Contents

<b>BS2_GetUserSmallInfosExFromDir</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

[USB Exported Control API](#) > [BS2\\_GetUserSmallInfosExFromDir](#)

---

## BS2\_GetUserSmallInfosExFromDir

[+ 2.6.3] Gets the user information of the given user ID from USB exported data. (Including Job, phrase)

The only difference between with [BS2\\_GetUserInfosExFromDir](#) which is using structure [BS2UserBlobEx](#) is that the 5th parameter `BS2UserPhoto` of `BS2UserSmallBlobEx` is using pointer for efficient memory use.

### Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosExFromDir(void* context, const char* szDir, char*
uids, uint32_t uidCount, BS2UserSmallBlobEx* userBlob);
```

[See BS2UserSmallBlobEx Structure](#)

### Parameter

- [In] *context* : Context
- [In] *szDir* : Storage path in device
- [In] *uids* : User ID list trying to get
- [In] *uidCount* : Number of user ID
- [Out] *userBlob* : Pointer to store the user information

### Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned.

### See Also

[BS2\\_GetUserSmallInfosFromDir](#)  
[BS2\\_GetUserSmallDatasFromDir](#)  
[BS2\\_GetUserSmallInfosExFromDir](#)  
[BS2\\_GetUserSmallDatasExFromDir](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_getusersmallinfosexfromdir&rev=1560326544](http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_getusersmallinfosexfromdir&rev=1560326544)

Last update: **2019/06/12 17:02**