Table of Contents

BS2_GetUserSmallInfosExFromDirWithKey

[+2.8.2] Gets the user information corresponding to the user identifier from the data extracted by USB.
The difference from BS2_GetUserInfosExFromDirWithKey that uses BS2UserBlobEx is
For memory efficiency, all are the same except that the fifth factor BS2UserSmallBlobEx member BS2UserPhoto is pointer-processed.

Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosExFromDirWithKey(void* context, const char* szDir,
char* uids, uint32_t uidCount, BS2UserSmallBlobEx* userBlob, const
BS2EncryptKey* key);
```

> View the structure of the BS2UserSmallBlobEx

Parameters

- [In] *context* : Context
- [In] *szDir* : Data storage path
- [In] *uids* : List of user identifiers to be imported
- [In] *uidCount* : Number of user identifiers
- [Out] *userBlob* : Pointer to store user information
- [In] *key* : Encryption key and the key value specified by BS2_SetDataEncryptKey.

Return value

Returns BS_SDK_SUCCESS if performed successfully, or a corresponding error code if an error occurs.

See Also

BS2_GetUserSmallInfosFromDirWithKey
BS2_GetUserSmallDatasFromDirWithKey
BS2_GetUserSmallInfosExFromDirWithKey

BS2_GetUserSmallDatasExFromDirWithKey