

# Table of Contents

<b>BS2_GetUserSmallInfosFromDirWithKey</b> .....	1
Declaration .....	1
Parameters .....	1
Return value .....	1
Watch Together .....	1

[USB Exported Control API](#) > [BS2\\_GetUserSmallInfosFromDirWithKey](#)

---

## BS2\_GetUserSmallInfosFromDirWithKey

[+2.8.2] Gets the user information corresponding to the user identifier from the data extracted by USB.

[BS2UserBlob](#) The difference from [BS2\\_GetUserInfosFromDirWithKey](#) is

For memory efficiency, all are the same except that the fifth factor [BS2UserSmallBlob](#) member [BS2UserPhoto](#) is pointer-processed.

### Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosFromDirWithKey(void* context, const char* szDir,
char* uids, uint32_t uidCount, BS2UserSmallBlob* userBlob, const
BS2EncryptKey* key);
```

[View the structure of the BS2UserSmallBlob](#)

### Parameters

- [In] *context* : Context
- [In] *szDir* : Data storage path
- [In] *uids* : List of user identifiers to be imported
- [In] *uidCount* : Number of user identifiers
- [Out] *userBlob* : Pointer to store user information
- [In] *key* : Encryption key and the key value specified by [BS2\\_SetDataEncryptKey](#)

### Return value

Returns [BS\\_SDK\\_SUCCESS](#) if performed successfully, or a corresponding error code if an error occurs.

### Watch Together

[BS2\\_GetUserSmallInfosFromDirWithKey](#)

[BS2\\_GetUserSmallDatasFromDirWithKey](#)

[BS2\\_GetUserSmallInfosExFromDirWithKey](#)

[BS2\\_GetUserSmallDatasExFromDirWithKey](#)

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[https://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2\\_getusersmallinfosfromdirwithkey&rev=1650348172](https://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_getusersmallinfosfromdirwithkey&rev=1650348172)

Last update: **2022/04/19 15:02**