

Table of Contents

BS2_GetVoipConfigExt

Declaration

Parameter

Return Value

.....

.....

.....

.....

1

1

1

1

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

[Configuration API](#) > [BS2_GetVoipConfigExt](#)

BS2_GetVoipConfigExt

[+ 2.8.3] BioStation 3 Gets the extended VoIP settings.

[BS2VoipConfig](#) comparing Various settings have been added, such as specifying outbound proxy and setting the volume.

Declaration

```
#include "BS_API.h"

int BS2_GetVoipConfigExt(void* context, uint32_t deviceId, BS2VoipConfigExt* config);
```

[BS2VoipConfigExt View Structures](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device Identifier
- [Out] *config* : Pointer to store VoIP settings information

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_getvoipconfigext&rev=1661428266

Last update: **2022/08/25 20:51**