

Table of Contents

BS2_SetDataEncryptKey	1
Declaration	1
Parameter	1
Return Value	1
See Also	1

[SDK API](#) > [BS2_SetDataEncryptKey](#)

BS2_SetDataEncryptKey

[+ V2.6.0] Sets data encryption key.

If the device's key is the same as the one you are currently setting, the key setting will be ignored. Also, if the key of the device is different from the one you want to set, the key will be set and the device's data will be erased.

Declaration

```
#include "BS_API.h"

int BS2_SetDataEncryptKey(void* context, uint32_t deviceId, const
BS2EncryptKey* keyInfo);
```

[See BS2EncryptKey Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *keyInfo* : The address of the key information structure to set.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_GetDataEncryptKey](#)

[BS2_RemoveDataEncryptKey](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_setdataencryptkey&rev=1523865445

Last update: **2018/04/16 16:57**