

## Table of Contents

<b>BS2_SetDefaultResponseTimeout</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

[Communication API > BS2\\_SetDefaultResponseTimeout](#)

---

## BS2\_SetDefaultResponseTimeout

[+ 2.6.3] Sets default response timeout between device and server. It defines timeout of every API except connection(hardcoded 3s) and BS2\_GetFilteredLog(300s).

### Declaration

```
#include "BS_API.h"

int BS2_SetDefaultResponseTimeout(void* context, long ms);
```

### Parameter

- [In] *context* : Context
- [In] *ms* : Respond waiting time (milli seconds)

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_GetDefaultResponseTimeout](#)

From:  
<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:  
[http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_setdefaultresponsetimeout&rev=1562648707](http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_setdefaultresponsetimeout&rev=1562648707)

Last update: **2019/07/09 14:05**