

## Table of Contents

<b><i>BS2_SetIPConfigViaUDPEx</i></b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1

Configuration API > [BS2\\_SetIPConfigViaUDPEx](#)

## BS2\_SetIPConfigViaUDPEx

[+ 2.6.3] Stores IP configuration through UDP broadcast with host IP.  
It is useful on systems with multiple Ethernet cards installed.

### Declaration

```
#include "BS_API.h"

int BS2_SetIPConfigViaUDPEx(void* context, uint32_t deviceId, const
BS2IpConfig* config, const char* hostipAddr);
```

See [BS2IpConfig Structure](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : IP configuration pointer
- [In] *hostipAddr* : Host IP address

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_setipconfigviaudpex](http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_setipconfigviaudpex)

Last update: **2019/06/18 10:21**