

Table of Contents

BS2_SetTimedAntiPassbackZone	1
Declaration	1
Parameter	1
Return Value	1
See Also	1

[Zone Control API](#) > [BS2_SetTimedAntiPassbackZone](#)

BS2_SetTimedAntiPassbackZone

Configures a timed Anti Passback zone.

Declaration

```
#include "BS_API.h"

int BS2_SetTimedAntiPassbackZone(void* context, uint32_t deviceId,
BS2TimedAntiPassbackZone* zones, uint32_t zoneCount);
```

[See BS2TimedAntiPassbackZone Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *zones* : List of timed Anti Passback zones
- [In] *zoneCount* : Number timed of Anti Passback zones

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.
If there is an error, the corresponding error code will be returned.

See Also

[BS2_GetTimedAntiPassbackZone](#)
[BS2_GetAllTimedAntiPassbackZone](#)
[BS2_GetTimedAntiPassbackZoneStatus](#)
[BS2_GetAllTimedAntiPassbackZoneStatus](#)
[BS2_SetTimedAntiPassbackZoneAlarm](#)
[BS2_RemoveTimedAntiPassbackZone](#)
[BS2_RemoveAllTimedAntiPassbackZone](#)
[BS2_ClearTimedAntiPassbackZoneStatus](#)
[BS2_ClearAllTimedAntiPassbackZoneStatus](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_settimedantipassbackzone

Last update: **2016/07/12 09:42**