

## Table of Contents

|  |   |
|--|---|
| <b><i>BS2_SetTriggerActionConfig</i></b> ..... | 1 |
| Declaration .....                              | 1 |
| Parameter .....                                | 1 |
| Return Value .....                             | 1 |

Configuration API > [BS2\\_SetTriggerActionConfig](#)

## BS2\_SetTriggerActionConfig

Stores trigger and action settings on the device.

### Declaration

```
#include "BS_API.h"

int BS2_SetTriggerActionConfig(void* context, uint32_t deviceId,
BS2TriggerActionConfig* config);
```

[See BS2TriggerActionConfig Structure](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : Trigger and action configurations pointer

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_settriggeractionconfig](http://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_settriggeractionconfig)

Last update: **2016/07/12 09:08**