

# Table of Contents

<b>BS2_StartMonitoringLogEx</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.  
(remove this paragraph once the translation is finished)

[Log Management API](#) > [BS2\\_StartMonitoringLogEx](#)

---

## BS2\_StartMonitoringLogEx

[+ V2.7.1] Starts Real-time log streaming including the temperature information.

### Declaration

```
#include "BS_API.h"

int BS2_StartMonitoringLogEx(void* context, uint32_t deviceId,
OnLogReceivedEx ptrLogReceivedEx);
```

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *ptrLogReceivedEx* : Callback function that is called when a new log is received

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_StopMonitoringLog](#)

From:  
<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2\\_startmonitoringlogex&rev=1599721518](https://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_startmonitoringlogex&rev=1599721518)

Last update: **2020/09/10 16:05**