

Table of Contents

<i>BS2_UpgradeFirmware</i>	1
Declaration	1
Parameter	1
Return Value	1

Device API > BS2_UpgradeFirmware

BS2_UpgradeFirmware

Upgrades the firmware.

Declaration

```
#include "BS_API.h"

int BS2_UpgradeFirmware(void* context, uint32_t deviceId, uint8_t*
firmwareData, uint32_t firmwareDataLen, uint8_t keepVerifyingSlaveDevice,
OnProgressChanged ptrProgressChanged);
```

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *firmwareData* : Firmware data
- [In] *firmwareDataLen* : Size of the firmware data
- [In] *keepVerifyingSlaveDevice* : Flag that decides whether to enable the authentication on the slave device when upgrading the resource
- [In] *ptrProgressChanged* : progress change listener

NOTE

keepVerifyingSlaveDevice parameter needs to be checked whether it is supported from the firmware.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

From:

<http://kb.supremainc.com/bs2sdk/> - BioStar 2 Device SDK

Permanent link:

http://kb.supremainc.com/bs2sdk./doku.php?id=en:bs2_upgradefirmware

Last update: 2016/04/20 09:34

