

Table of Contents

BS2_VerifyUserEx	1
Declaration	1
Parameter	1
Return Value	1
See Also	1

[Server API](#) > [BS2_VerifyUserEx](#)

BS2_VerifyUserEx

Transfers user information mapped to the card or user ID authentication results to the device.

Declaration

```
#include "BS_API.h"

int BS2_VerifyUserEx(void* context, uint32_t deviceId, uint16_t seq, int
handleResult, BS2UserBlobEx* userBlob);
```

[See BS2UserBlobEx Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence number
- [In] *handleResult* : Value of matching result(BS_SDK_SUCCESS or BS_SDK_ERROR_XXX)
- [In] *userBlob* : Matched user information

NOTE

Packet sequence number must be equivalent to the value sent from the OnVerifyUser.

If the handleResult is BS_SDK_SUCCESS, the userBlob should not be null.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_SetServerMatchingHandler](#)

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=en:bs2_verifyuserex

Last update: **2017/03/21 11:39**