

# Table of Contents

|                           |   |
|---------------------------|---|
| <b>Device API</b> .....   | 1 |
| <b>Structure</b> .....    | 1 |
| BS2SimpleDeviceInfo ..... | 1 |
| BS2ResourceElement .....  | 4 |

# Device API

API that controls the device information or upgrade the firmware.

- [BS2\\_GetDeviceInfo](#): Gets the device information.
- [BS2\\_GetDeviceTime](#): Gets the device time.
- [BS2\\_SetDeviceTime](#): Sets the device time.
- [BS2\\_ClearDatabase](#): Initializes the user information and blacklist.
- [BS2\\_FactoryReset](#): Initializes all configurations and the database.
- [BS2\\_RebootDevice](#): Restarts the device.
- [BS2\\_LockDevice](#): Doesn't allow user authentication by locking the device.
- [BS2\\_UnlockDevice](#): Allows user authentication by unlocking the device.
- [BS2\\_SetKeepAliveTimeout](#): Configures the keep-alive time of the device.
- [BS2\\_UpgradeFirmware](#): Upgrades the firmware.
- [BS2\\_UpdateResource](#): Updates the resource.

## Structure

### BS2SimpleDeviceInfo

```
typedef struct
{
    uint32_t id;
    uint16_t type;
    uint8_t connectionMode;
    uint32_t ipv4Address;
    uint16_t port;
    uint32_t maxNumOfUser;
    uint8_t userNameSupported;
    uint8_t userPhotoSupported;
    uint8_t pinSupported;
    uint8_t cardSupported;
    uint8_t fingerSupported;
    uint8_t faceSupported;
    uint8_t wlanSupported;
    uint8_t tnaSupported;
    uint8_t triggerActionSupported;
    uint8_t wiegandSupported;
    uint8_t imageLogSupported;
    uint8_t dnsSupported;
    uint8_t jobCodeSupported;
    uint8_t wiegandMultiSupported;
    uint8_t rs485Mode;
    uint8_t sslSupported;
    uint8_t rootCertExist;
    uint8_t dualIDSupported;
    uint8_t useAlphanumericID;
```

```

uint32_t connectedIP;
uint8_t phraseCodeSupported;
uint8_t card1xSupported;
uint8_t systemExtSupported;
uint8_t voipSupported;
}BS2SimpleDeviceInfo;

```

### 1. **id**

The device identifier which is always above 1.

### 2. **type**

Code value of device type.

| Value | Description   |
|-------|---------------|
| 0x01  | BioEntry Plus |
| 0x02  | BioEntry W    |
| 0x03  | BioLite Net   |
| 0x04  | Xpass         |
| 0x05  | Xpass S2      |
| 0x06  | Secure IO 2   |
| 0x07  | DM-20         |
| 0x08  | BioStation 2  |
| 0x09  | BioStation A2 |
| 0x0A  | FaceStation 2 |
| 0x0B  | IO Device     |
| 0x0C  | BioStation L2 |
| 0x0D  | BioEntry W2   |
| 0x0E  | CoreStation   |
| 0x0F  | Output Module |
| 0x10  | Input Module  |
| 0x11  | BioEntry P2   |
| 0x0F  | OM-120        |

### 3. **connectionMode**

It indicates the connection mode between the BioStar application and device which is separated by the subject of the connection as direct mode(0x0) and server mode(0x1). The BioStar application connects to the device in direct mode, and the device connects to the BioStar application in server mode. The default settings for the devices are direct mode, and to change the connection mode refer to [IP Config](#).

### 4. **ipv4Address**

IP address of the selected device.

### 5. **port**

TCP port number of the selected device.

### 6. **maxNumOfUser**

Maximum capacity of users that can be stored in the device.

### 7. **userNameSupported**

Flag that notifies whether the device supports user name.

**8. *userPhotoSupported***

Flag that notifies whether the device supports user profile picture.

**9. *pinSupported***

Flag that notifies whether the device supports PIN.

**10. *cardSupported***

Flag that notifies whether the device supports Smart card authentication.

**11. *fingerSupported***

Flag that notifies whether the device supports finger authentication.

**12. *faceSupported***

Flag that notifies whether the device supports face recognition.

**13. *wlanSupported***

Flag that notifies whether the device supports wireless LAN.

**14. *tnaSupported***

Flag that notifies whether the device supports time and attendance.

**15. *triggerActionSupported***

Flag that notifies whether the device supports trigger action.

**16. *wiegandSupported***

Flag that notifies whether the device supports wiegand.

**17. *imageLogSupported***

Flag that notifies whether the device supports image logs.

**18. *dnsSupported***

Flag that notifies whether the device supports DNS.

**19. *jobCodeSupported***

Flag that notifies whether the device supports job codes.

**20. *wiegandMultiSupported***

Flag that notifies whether the device supports Multi-Wiegand.

**21. *rs485Mode***

**RS-485 mode of the device.**

**22. *sslSupported***

Flag that notifies whether the device supports SSL communication.

**23. *rootCertExist***

**Flag that notifies whether the device has a root certificate.**

**24. *dualIDSupported***

Flag that notifies whether the device supports alphanumeric ID.

**25. *useAlphanumericID***

**Flag that notifies whether the device is currently using Alphanumeric ID.**

**26. *connectedIP***

IP address where the device is connected to. (0xFFFFFFFF if disconnected)

**27. *phraseCodeSupported***

Flag that notifies whether the device supports personal messages.

**28. *card1xSupported***

Flag that notifies whether the device supports reading 1.x ToC cards.

**29. *systemExtSupported***

Flag that notifies whether the device supports configuring RS-485 keys.

**30. *voipSupported***

Flag that notifies whether the device supports VoIP.

**BS2ResourceElement**

```
typedef struct
{
    uint8_t type;
    uint32_t numResData;
    struct {
        uint8_t index;
        uint32_t dataLen;
        uint8_t* data;
    } resData[128];
}BS2ResourceElement;
```

**1. *type***

Resource data type.

| Value | Description       | Supported data format |
|-------|-------------------|-----------------------|
| 0     | UI(Language pack) | Suprema language pack |
| 1     | Notice message    | UTF-8 string          |
| 2     | Image(Background) | PNG                   |
| 3     | Slide image       | PNG                   |
| 4     | Sound             | WAVE                  |

**2. *numResData***

Number of resource data.

**3. *index***

Resource index number.

**4. *dataLen***

Resource data length.

**5. *data***

Binary resource data.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk/doku.php?id=en:device\\_api&rev=1504685575](http://kb.supremainc.com/bs2sdk/doku.php?id=en:device_api&rev=1504685575)

Last update: **2017/09/06 17:12**