

Table of Contents

Version 2.6.4 (V2.6.4.1)	1
Date	1
New Features	1
Modified Features	1

Version 2.6.4 (V2.6.4.1)

Date

2020-02-25

New Features

- Supports the API retrieving logs filtered by EventMask
- Supports DesFire Advanced format setting
- Supports the card type selection feature
- Supports duplicate fingerprints/face check

1. The API retrieving logs filtered by Event Mask so that you can use memory efficiently than before.

- Structure [BS2EventSmallBlob](#) has been added
- API [BS2_GetLogSmallBlob](#) has been added
- API [BS2_GetLogSmallBlobFromDir](#) has been added

2. DesFire Advanced format setting is now supported.

- Structure [BS2SimpleDeviceInfoEx](#) has been added
- Structure [BS2DesFireCardConfigEx](#) has been added
- API [BS2_GetDesFireCardConfigEx](#) has been added
- API [BS2_SetDesFireCardConfigEx](#) has been added

3. Card type selection is available so that you can select/deselect the card type you want to read from the device.

- Structure [BS2SystemConfig](#) has been added
- API [BS2_SetSystemConfig](#) has been added

4. Duplicate fingerprint and face check is available.

- Structure [BS2FaceConfig](#) has been added
- API [BS2_GetFingerprintConfig](#) has been added
- API [BS2_SetFingerprintConfig](#) has been added
- Structure [BS2FingerprintConfig](#) has been added
- API [BS2_GetFaceConfig](#) has been added
- API [BS2_SetFaceConfig](#) has been added

Modified Features

1. Fixed the issue of device malfunctioning and rebooting when BS2Job.numJobs in BS2UserBlobEx

exceeds the maximum value 16.

- Refer to structure [BS2UserBlobEx](#)
- Refer to API [BS2_VerifyUserEx](#)
- Refer to API [BS2_IdentifyUserEx](#)
- Refer to API [BS2_EnrolUserEx](#)
- Refer to API [BS2_VerifyUserSmallEx](#)
- Refer to API [BS2_IdentifyUserSmallEx](#)
- Refer to API [BS2_EnrollUserSmallEx](#)

2. Fixed the issue of BioStation 2 not available for user images.

3. Fixed the error BS_SDK_INVALID_CODE_SIGN when upgrading SIO2.

4. Fixed the error BS_SDK_ERROR_NOT_SUPPORTED when calling BS2_GetCardModel for BLN2-PAB.

- Refer to API [BS2_GetCardModel](#)

5. Fixed the issue that SDK doesn't recognize device disconnection when the device is constantly disconnected.

6. Fixed the issue of Linux SDK crash.

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk./doku.php?id=en:release_note_2640

Last update: **2020/03/03 13:10**