

Table of Contents

Version 2.8.1 (V2.8.1.0)	1
Date	1
New Features	1
Modified Features	1

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

Version 2.8.1 (V2.8.1.0)

Date

2021-08-05

New Features

- Supports X-Station 2 Finger
- Supports Input Module 120 Feature
- Supports the function of commanding certain actions to devices

1. X-Station 2 Finger Configurations are available to use.

2. Input Module 120 Configurations are available to use.

- Refer to Structure [BS2InputConfigEx](#)
- Refer to Structure [BS2RelayActionConfig](#)
- Refer to Structure [BS2Event relayAction](#)
- Refer to API [BS2_GetInputConfigEx](#)
- Refer to API [BS2_SetInputConfigEx](#)
- Refer to API [BS2_GetRelayActionConfig](#)
- Refer to API [BS2_SetRelayActionConfig](#)

3. You can now command certain actions to devices.

You can now turn on LED, alarm a buzzer, or control relay and perform more actions at the desired time with the COMMANDS below.

- Refer to Structure [BS2Action](#)
- Refer to API [BS2_RunAction](#)

Modified Features

1. Fixed the error in which Linux returns `BS_SDK_ERROR_TIMEOUT` and is not able to have device connections.

2. C# examples provided to guide through server-matching function implementation will not be supported anymore.

- Refer to the Server API Document [Server API](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=en:release_note_281&rev=1628205800

Last update: **2021/08/06 08:23**