

BS2_ClearDeviceZoneAccessRecord 1
..... 1
..... 1
..... 1
..... 1

BS2_ClearDeviceZoneAccessRecord

Ethernet

```
#include "BS_API.h"

int BS2_ClearDeviceZoneAccessRecord(void* context, uint32_t deviceId,
uint32_t zoneID, char* uids, uint32_t uidCount);
```

- [In] *context* : Context
- [In] *deviceId* :
- [In] *zoneID* :
- [In] *uids* : user ID
- [In] *uidCount* : user ID

BS_SDK_SUCCESS , 가

- [BS2_GetDeviceZone](#)
- [BS2_GetAllDeviceZone](#)
- [BS2_SetDeviceZone](#)
- [BS2_RemoveDeviceZone](#)
- [BS2_SetAntiPassbackZone](#)
- [BS2_RemoveAllDeviceZone](#)
- [BS2_SetDeviceZoneAlarm](#)
- [BS2_ClearAllDeviceZoneAccessRecord](#)

From: <http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link: http://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_cleardevicezoneaccessrecord&rev=1504534199

Last update: **2017/09/04 23:09**

